



# LD ROLLS



# LD Rolls

A lightweight roadway system for short-term use



<b>Material:</b>	strand-cast aluminum
<b>Dimensions (l x w x h):</b>	20.00 x 3.00 x 0.02 m (65 ft 7 in x 9 ft 10 in x 1 in)
<b>Weight:</b>	approx. 1,215.00 kg per 20.00 m roll (2,678 lbs per 65 ft roll)
<b>Surface:</b>	lightly textured, pedestrian friendly
<b>Accessories:</b>	PE foil, geotextile, rubber matting
<b>Transport:</b>	240.00 m (787 ft 4,82 in) (12 rolls) per truck (720.00 m <sup>2</sup> / 7,750.0 ft <sup>2</sup> )

## Applications

LD rolls are an excellent solution for providing short-term access routes for light- to medium-heavy loads. The rolled trackway allows for the rapid creation of lightweight roads and access points, providing incredible flexibility.

## Features

LD Rolls can be deployed, collected and redeployed within minutes, allowing for repeated use across event and construction sites.

Their ultra-thin design minimizes trip hazards, with a lightly treaded surface that prevents slipping, making LD Rolls safe for wheelchair, bicycle, forklift, and crane access.

## Optional Extras

- eps offers an optional range of underlays to protect the sub-surface and adapt to ground conditions
- eps offers CAD design to help expedite and optimize the planning process



**01** Rolled trackway allows for the fast creation of lightweight roads and access points | **02** LD Rolls can be deployed, collected and redeployed within minutes, allowing for repeated use across event or construction sites | **03** Easy installation makes LD Rolls suitable for dry hire | **04** A lightly treaded surface prevents slipping, making LD Rolls safe for wheelchair, bicycle, forklift, and crane access



**WHEREVER  
YOU GO, WE  
ARE THERE...**