



# REMOPLA



# Remopla

Load-bearing drivable event flooring for sensitive, level surfaces



<b>Material:</b>	recycled soft PVC, flame-retardent
<b>Dimensions (l x w x h):</b>	loading size: 1.20 x 0.80 m (47 x 32 in) cover size: 1.15 x 0.75 x 0.042 m (45 x 30 x 2 in)
<b>Weight:</b>	approx. 32.00 kg (70 lbs) per panel
<b>Color:</b>	standard in anthracite grey
<b>Accessories:</b>	ramps for smooth vehicle access, PE foil, geotextile
<b>Transport:</b>	30 per (euro) pallet 24 pallets per truck (620.00 m <sup>2</sup> / 6,674 ft <sup>2</sup> )

## Applications

Remopla heavy-duty floor panels are ideal for creating temporary access paths, work platforms, and parking lots, especially on flat, sensitive surfaces such as running tracks, tennis courts, or stadium floors. They can also be used as a foundation for stages and grandstands, or as an underlay for earth and sand at indoor motocross or equestrian events.

## Features

Remopla is made of recycled PVC with UV stabilizers. The treaded surface provides traction and prevents slipping. When laid on flat ground, Remopla creates a continuous, gap-free surface.

## Optional Extras

To protect extra-sensitive surfaces, we offer PE foil or geotextile as an additional protective underlay. eps also offers installation, cleaning, and collection, upon request.



01



02



03



04

01 Remopla robust floor protection panels optimally cover sensitive and, in particular, firm even surfaces | 02 Under appropriate circumstances, the panels can withstand heavy loads such as mobile cranes, trucks or forklifts | 03 For optimal adaptation to local conditions, the panels can also be cut to size | 04 In addition, the panels are characterized by a nubbed surface and thus offer particularly good traction

© eps

**WHEREVER  
YOU GO, WE  
ARE THERE...**