



Shower Facilities



Shower Facilities

Portable hot-water showers for multi-day events



Material:	Side and partition walls: Dibond panel Floor: ribbed aluminum panels
Dimensions (l x w x h):	5.00 x 2.00 x 2.20 m (16 ft 5 in x 6 ft 7 in x 7 ft 3 in)
Accessories:	Shower-stall dividers, shower curtains, shower containers, tents, and storage shelves
Additional Information:	Water connections: Inlet water: knuckle coupling (2") Grey water: sewage pipe 100 mm (4 in)
Transport:	12 shower modules per standard trailer Equivalent to 144 shower units

Applications

Our extremely sturdy shower modules have been custom-designed by eps by eps for large, multi-day events, such as festivals and sporting tournaments. They are particularly well-suited for use in campgrounds and backstage areas.

Features

Each shower module is made up of 12 shower units (six on either side) and features an instant water heater that provides water at 37° Celsius (98° Fahrenheit). To conserve water, showerheads are fitted with self-closing valves and can be programmed to automatically shut off after an interval of between five and 50 seconds. The modules are also outfitted with ribbed aluminum flooring, which protects against slipping. They can be connected to an exterior water supply through a 2-inch threaded pipe. For ease of installation, The modules are

constructed from small interlocking components that can be easily loaded and positioned with a forklift.

Optional Extras

We offer planning services, delivery, hook up, waste disposal, cleaning, and collection. Upon request, the shower stalls can be equipped with secure divider walls and additional shower curtains. If there is no existing water supply or sewage system at your event site, we can provide portable solutions, such as holding tanks.



01 Each shower module comprises of twelve shower units, each with six individual shower cubicles on each side | **02** Shower modules are separated using partitions and curtains with partitions and curtains | **03** The flooring is made from sturdy, non-slip aluminum checker plate | **04** The water flow can be programmed to automatically shut off after between 5 to 50 seconds

**WHEREVER
YOU GO, WE
ARE THERE ...**