

# Plywood

## Versatile wood panels for medium loads

|                    |                                                                                                                                                            |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Material</b>    | uncoated, glued wooden board (Elliotis Pine)                                                                                                               |
| <b>Dimensions</b>  | area: ca. 3.00 m <sup>2</sup> (32 ft <sup>2</sup> )<br>cover size: ca. 2.44 × 1.22 m (8 × 4 ft)<br>depth: 0.024 m (1 in)                                   |
| <b>Weight</b>      | approx. 35.00 kg (77 lbs) dry<br>up to 50.00 kg (110 lbs) damp                                                                                             |
| <b>Color</b>       | natural                                                                                                                                                    |
| <b>Accessories</b> | PE foil, Geotextile, special ramps (steel)                                                                                                                 |
| <b>Transport</b>   | stack of up to 50 panels (150.00 m <sup>2</sup> /1,615 ft <sup>2</sup> )<br>approx. 1,800.00 m <sup>2</sup> (19,375 ft <sup>2</sup> ) per standard trailer |



### Applications

Plywood is a versatile, low-cost ground cover for light and medium loads. It is ideal for temporary transport routes, such as mixer path, or for building foundations for small stages and grandstands. When multiple layers are bolted together, it can also be used to build construction ramps, drain covers, and temporary access roads for heavy vehicles.

### Features

Plywood consists of thin layers of wood that are glued and pressed into a single panel. A relatively lightweight material, it is easy to transport and can be installed by hand. However, because sunlight and air cannot penetrate the wood, turf and other sensitive foliage should be covered for a maximum of two days.

### Optional Extras

Upon request, we offer delivery, installation, dismantling, and pickup. To protect against damage and staining, we recommend a PE foil or Geo textile underlay.



# Plywood

## On-site applications



*Temporary access road for forklifts and cranes*



*A plywood walkway*



*A plywood transport path for rolling cases and supply vehicles*



*Plywood being installed for an Elton John concert, Copenhagen, Denmark*



*Plywood ground cover for the Summerjam Festival, Cologne, Germany*

© eps